

Declare.

Calla® Ceiling Panels Armstrong World Industries, Inc.

Final Assembly: Pensacola, Florida, USA; Marietta, Pennsylvania, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.305 kg CO₂eq 

Declared Unit: square foot

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program)

Ingredients:

Mineral Wool; Perlite; Corn Starch; Clay; Cellulose; Calcium Carbonate; Limestone; Aluminum hydroxide; Aluminum Trihydrate; Polyvinyl acetate; Titanium dioxide; Acrylic Acid; Calcium carbonate; Barium sulfate; Propanol; Starch; Zinc borate; Polyvinyl alcohol; Kaolin; Silica; Diatomaceous Earth; Quartz; Polyethylene Wax; Amorphous Silica; Mica; Sodium Salt; Hydroxyethylcellulose; Paraffin Wax; Black Tint; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Silicic Salt; Attapulgite Clay; Iron Oxide; Water; Methylpropanoate; Oxirane, 2-phenyl-, polymer with oxirane, mono(dihydrogen phosphate), decyl ether; Butanamide, N-(4-chloro-2,5-dimethoxyphenyl) -2-[[2,5-dimethoxy-4-[(phenylamino)sulfonyl]phenyl]azo]-3-oxo-

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

ARM-0001

EXP. 01 APR 2025

Original Issue Date: 2016