

Declare. SM

Clean Room™ Suspension System (Aluminum) Armstrong World Industries

Final Assembly: Aberdeen, Maryland, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 9.85 kg CO₂eq 

Declared Unit: 1 linear meter

End of Life Options: Recyclable (100%)

Ingredients:

Aluminum Powder; Benzene, ethenyl-, polymer with 1,3-butadiene, hydrogenated; 1,4-Benzenedicarboxylic acid, dimethyl ester, polymer with 1,4-butanediol and α -hydro- ω -hydroxypoly(oxy-1,4-butanediyl); White mineral oil (petroleum); Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester; Calcium Carbonate; Phenol, 2,4-bis(1,1-dimethylethyl)-, phosphite (3:1); Magnesium; Manganese; Silicon; Iron Oxide; White Tint; Iron; Chromium, metallic; Copper; Zinc; Petroleum distillates; Titanium; 2-Butoxyethanol; Octadecanoic acid, calcium salt; Butanol; Ethanol; Naphtha; Trimethylbenzenes; Xylene; C.I. Pigment Yellow 53; Ethylbenzene

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0098

EXP. 01 APR 2025

Original Issue Date: 2024