

Cortega[®] Ceiling Panels Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA; Macon, Georgia,

USA; Pensacola, Florida, USA Life Expectancy: 30 Year(s)

Embodied Carbon: 0.216 kg CO2e/ft2

Declared Unit: square foot

End of Life Options: Take Back Program (Armstrong Ceiling

Recycling Program), Recyclable (100%)

Ingredients:

Perlite; Cellulose; Mineral Wool; Clay; Glass, oxide, chemicals; Corn Starch; Calcium Carbonate; Starch, 2-hydroxyethyl ether; Acrylic Acid; Silica; Diatomaceous Earth; Starch; Hydroxy starch; Water; Fatty Acids; Quartz; Limestone; Polyethylene Wax; Sodium Salt; Chlorite-group minerals; Talc; Polyvinyl acetate; Lubricating oil; Lubricating Oil

Living Building Challenge Criteria: Compliant

I-13 Red List:

■ LBC Red List Free % Disclosed: 100% at 100ppm

☐ LBC Red List Approved VOC Content: Not Applicable

Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0043 EXP. 01 DEC 2024

Original Issue Date: 2019