

# Declare. SM

---

## Cortega® Fire Guard™ Ceiling Panels Armstrong World Industries

**Final Assembly:** Marietta, Pennsylvania, USA; Pensacola, Florida, USA

**Life Expectancy:** 30 Year(s)

**Embodied Carbon:** 0.216 kg CO<sub>2</sub>e/ft<sup>2</sup> ■

**Declared Unit:** square foot

**End of Life Options:** Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

### Ingredients:

---

Mineral Wool; Calcium Carbonate; Clay; Perlite; Quartz; Cellulose; Corn Starch; Titanium dioxide; Kaolin; Acrylic Acid; Silica; Diatomaceous Earth; Silisic Salt; Polyethylene Wax; Starch; Hydroxy starch; Water; Sodium Salt; Amorphous Silica; Aluminum hydroxide; Fatty Acids; Chlorite-group minerals; Talc; Sodium dimethyldithiocarbamate

**Living Building Challenge Criteria:** Compliant

---

### I-13 Red List:

- |   |                             |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved        | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared                     |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

ARM-0082

EXP. 01 MAY 2025

Original Issue Date: 2022

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ [living-future.org/declare](https://living-future.org/declare)