

Fine Fissured™ and Fine Fissured™ High NRC

Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA; Macon, Georgia,

USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.238 kg CO2 eq. Y

Declared Unit: 1 square foot

End of Life Options: Take Back Program (Armstrong Ceiling

Recycling Program), Recyclable (100%)

Ingredients:

Perlite; Cellulose; Mineral Wool; Glass, oxide, chemicals; Clay; Calcium Carbonate; Corn Starch; Hydroxy starch; Water; Silica; Diatomaceous Earth; Starch; Fatty Acids; Polyvinyl acetate; Starch, 2-hydroxyethyl ether; Quartz; Acrylic Acid; Proprietary Ingredient (< 0.06%)¹; Lubricating oil

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

% Disclosed: 99.94% at 100ppm VOC Content: Not Applicable

LBC Red List Approved

Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0050 EXP. 01 JUL 2024

Original Issue Date: 2019