

Declare.

Lyra™ PB High CAC Ceiling Panels Armstrong World Industries

Final Assembly: Hilliard, Ohio, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.681 kg CO2 eq. 

Declared Unit: 1 square foot

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Glass, oxide, chemicals; Mineral Wool; Clay; Perlite; Starch, polymer with 2-propenoic acid, graft, sodium salt; Quartz; Cellulose; Corn Starch; Fats and Glyceridic oils, vegetable, polymd., oxidized; Calcium Carbonate; Aluminum hydroxide; Titanium dioxide; Polyvinyl acetate; Siloxane; Propanol; Polyvinyl alcohol; Acrylic Acid; Proprietary Ingredient (< 0.1%)¹; Aluminum Trihydrate; Limestone; Water; Calcium carbonate; Mica; Silica; Diatomaceous Earth

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|------------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99.9% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0018

EXP. 01 AUG 2024

Original Issue Date: 2016