

CALLA® Health Zone™
AirAssure®
Tegular & Square Lay-in
smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Calla® Health Zone™ AirAssure® Square Tegular panels with Prelude® ML® 15/16" Exposed Tee suspension system

Seamlessly integrates with Armstrong VidaShield UV24™ Air Purification System to improve air quality

Smoothest mineral fiber ceiling available with factory-gasketed edges contributes to cleaner, safer, indoor air quality for every healthy space. Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines.

KEY SELECTION ATTRIBUTES

- Factory-gasketed edges reduce air leakage through the ceiling plane to direct airflow more effectively and improve indoor air quality
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface

- Improved sound blocking performance – provides some of the highest speech privacy in the Total Acoustics portfolio with a CAC 40.
- Clean + Simple - AirAssure® panels are part of the Sustain® portfolio and are free of Red List Chemicals for better indoor air quality
- Clean Room Performance up to ISO Class 5 (Class 100) using standard non-gasketed suspension systems

- Exceptional durability & cleanability – smooth, durable finish – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- AirAssure® ceilings enable easy conversion to negative or positive pressure-controlled spaces (without hold-down clips)
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth

TYPICAL APPLICATIONS

- Office – conference rooms, lobbies, cafe
- Education – nurses office, locker room, bathrooms
- Healthcare – patient rooms, nurses stations, treatment rooms
- Emergency rooms and 24-hour care
- Assisted living facilities
- Manufacturing control and break rooms
- Clean Rooms
- Pressure-controlled spaces

COLOR



White (WH)

DETAILS



1. Calla® Health Zone™ AirAssure® Square Lay-in
2. Calla® Health Zone™ AirAssure® Square Tegular
3. Calla® Health Zone™ AirAssure® Square Tegular with Suprafine® 9/16" suspension system

CALLA® Health Zone™ AirAssure®

Tegular & Square Lay-in
smooth texture



76% RECYCLED CONTENT

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

Item No.	Dimensions (Inches)	UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect*	Anti-Bacterial/Mold/Mildew	Humi-Guard+ Sag Resistant	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program	30-Yr Warranty
CALLA® Health Zone™ AirAssure® 15/16" Square Lay-in	2228 24 x 24 x 1" □ 2229 24 x 48 x 1" □	0.80 + 40 =	BEST	170	Class A	0.85	+	*	*	*	*	*
15/16" Square Tegular	1354 24 x 24 x 1" □ 1359 24 x 48 x 1" □	0.80 + 40 =	BEST	170	Class A	0.85	+	*	*	*	*	*
9/16" Square Tegular	1353 24 x 24 x 1" □ 1358 24 x 48 x 1" □	0.80 + 40 =	BEST	170	Class A	0.85	+	*	*	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)
* Advertised values for light reflectance, wash, scrub and scratch resistance are applicable to White panels only

AIR LEAKAGE DATA MEASURED IN UNITS OF [CFM/FT²]


Item No.	Suspension System	Air Leakage in [CFM/ft ²] Without Hold-down Clips (Item 442) @ 0.02 [in WC]	Air Leakage in [CFM/ft ²] With Hold-down Clips (Item 442) @ 0.02 [in WC]
2228	15/16" Prelude® XL®	0.81	0.45
2229	15/16" Prelude XL	0.37	0.20
1354	15/16" Prelude XL	0.36	0.21
1359	15/16" Prelude XL	0.16	0.11
1353	9/16" Suprafine®	0.41	0.27
1358	9/16" Suprafine	0.25	0.14

Positive pressures above 0.09 [in WC] may require use of hold-down clips
Questions? email Techline@armstrongceilings.com for more information and independent 3rd party test details.

ACCESSORIES (must be ordered separately)

Item No.	Description	Pcs
1350	AirAssure® Sealing Tape	25 ln/ft. roll
442	Vector Hold-down Clip	50

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber with acoustically transparent membrane and polyethylene foam.

Surface Finish
Acoustically transparent membrane with factory-applied latex paint.

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew
Ceiling panels with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling panel surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 2.9 (BTU units)
R Factor – 0.445 (Watts units)

Installation Considerations
See installation instructions for more information on field-cut tegular edges and guidance on AirAssure® sealing tape

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1354, 1353, 2228 – 1.0 lbs/SF; 40 SF/ctn
1358, 1359, 2229 – 1.02 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton



CEILING THAT IMPROVE IAQ