


CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Learn How Templok 
Ceilings Save Energy!*



Calla® Templok Beveled Tegular panels with Suprafine® 9/16" suspension system

Smooth texture mineral fiber ceiling combines exceptional acoustical performance, energy savings and enhanced thermal comfort using advanced Phase Change Material (PCM) technology.

KEY SELECTION ATTRIBUTES

- Saves up to 15% energy*
- Improve thermal comfort with ceilings that help regulate indoor temperatures
- Provides up to 35 BTUs/SF of passive cooling*
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance

- Exceptional sound-blocking performance for enhanced speech privacy: CAC 39
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Energy-saving, high light-reflective finish
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America Act (BABAA)

* Measured cooling energy savings in lab test. Results may vary. See Templok Technical Guide.

TYPICAL APPLICATIONS

- Office
- Education
- Transportation
- Healthcare

COLOR



White
(WH)

DETAILS (Other suspension systems compatible. Refer to listing on next page.)



1. Calla® Templok® Square Tegular panel
2. Calla Templok back of panel
3. Calla Templok with Suprafine® 9/16" suspension system

LEED® WELL | LBC

Up to **41% RECYCLED CONTENT**

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CALLA® Templok® 9/16" Square Tegular	29, 44, 48, 52, 56	2824TEMP (Field Panel Only – cannot be cut)	24 × 24 × 1-1/4" □
		2824 Use 2824 for borders and cutting needs. See Calla Tegular Data Page for Product Details	24 × 24 × 1" □
CALLA® Templok® 15/16" Square Tegular		2822TEMP (Field Panel Only – cannot be cut)	24 × 24 × 1-1/4" □
		2822 Use 2822 for borders and cutting needs. See Calla Tegular Data Page for Product Details	
Made-to-Order Calla® Templok® Panels		2820TEMP 24" × 24" 15/16" Square Lay-in Field Panel Only – cannot be cut. Use 2820 for borders and cutting needs. See Calla Lay-in Data Page for product details	1-1/4" Thick – 15/16" Square Lay-in

4-6 WEEKS
order to ship

1,000 SF minimum order quantity applies to Item 2820TEMP. 2820TEMP is the only made-to-order panel available. Custom sizes are not available.


PERFORMANCE SELECTION Dots represent high level of performance.

NRC	CAC	Total Acoustics ¹ NRC + CAC	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program	30-Yr Warranty			
0.85	39	BEST	170	Class A**	0.85	*	*	*	Fog	Wash	Impact	Scratch	Soil	Recycle Program	30-Yr Warranty
0.85	39	BEST	170	Class A**	0.85	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	170	Class A	0.85	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	170	Class A**	0.85	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	170	Class A	0.85	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	170	Class A	0.85	*	*	*	*	*	*	*	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

** Consult a code official in your jurisdiction for mechanical code compliance.

SUSPENSION SYSTEMS



Blizzard White – Suspension System Finish
A color and texture coordinated suspension system to complement Calla® ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material
Wet-formed mineral fiber with acoustically transparent membrane and virgin PVC with salt hydrate

Surface Finish
Acoustically transparent membrane with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 450 or less.

ASTM E1264 Classification
Type A5, Form 2, Pattern E

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

Thermal Performance
Stores up to 35 BTU/SF per ASTM C1784

VOC Emissions
Compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Silhouette® suspension system for 9/16" edge detail.

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Ten (10) Year Limited Thermal Energy Storage Capacity Warranty

Weight; Square Feet/Carton
2824TEMP – 2.25 LBS/SF; 16 SF/CTN
2822TEMP – 2.25 LBS/SF; 16 SF/CTN

Minimum Order Quantity
1 carton