

CIRRUS® High NRC
CIRRUS®
Square Lay-in
medium texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFLEX®
A New World of Choice
for Ceiling Systems



▲ Cirrus® Square Lay-in panels with Prelude® XL® 15/16" suspension system

See more photos at:
armstrongceilings.com/photogallery

Medium-texture panels offer both Sustain® and Total Acoustics® panel performance; Good noise reduction and sound blocking in one panel.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include made-to-order sizes available to ship in 3 weeks
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Refined visual
- Excellent combination of acoustical performance NRC up to 0.75 and CAC 35
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- High NRC items feature Articulation Class 170, helpful to control sound over wall partitions
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 574HRC and 533HRC. 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 91%

COLOR



White
(WH)

DETAILS



1. Cirrus® Square Lay-in
2. Cirrus® Square Lay-in with Prelude® XL® 15/16" suspension system

CIRRUS® High NRC CIRRUS®

Square Lay-in
medium texture



USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 91%

Declare.

SUSTAIN*
High Performance
Sustainable Ceiling Systems

GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC

UP TO **87%** RECYCLED CONTENT

Calculate sustainability with Green Genie®
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CIRRUS® High NRC 15/16" Square Lay-in	1	563	24 x 24 x 7/8" □
Made-to-Order Sizes CIRRUS® High NRC		Width	Length
		12" - 24"	24" - 48"
CIRRUS® 15/16" Square Lay-in	1	574 574HRC	24 x 24 x 3/4" □ 24 x 24 x 3/4"
Made-to-Order Sizes CIRRUS®		Width	Length
		12" - 24"	24" - 48"
CIRRUS® 15/16" Square Lay-in	1	533 533HRC	24 x 48 x 3/4" □ 24 x 48 x 3/4"
Made-to-Order Sizes CIRRUS®		Width	Length
		12" - 24"	24" - 48"

3-4 WEEKS
order to ship

1 Ctn Min FASTSIZE 3 WEEKS
order to ship


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Durability	Recycle Program	30-Yr Warranty
0.75	35	BETTER	170	Class A	0.84	*	*	*	Std	*	*
0.75	35	BETTER	170	Class A	0.84	*	Std	*	Std	*	10-Yr
N/A	N/A	N/A	N/A	Class A	0.84	*	Std	*	Std	*	10-Yr
0.70	35	BETTER	N/A	Class A	0.85	*	*	*	Std	*	*
0.70	35	BETTER	N/A	Class A	0.85	*	Std	*	Std	*	10-Yr
N/A	N/A	N/A	N/A	Class A	0.85	*	Std	*	Std	*	10-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 1, Pattern E I
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications. Excludes items 533, 533HRC, 565, and large sizes.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustic Performance
CAC testing conducted using Prelude® suspension system.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value
R Factor - 1.9 (BTU units); R Factor - 0.33 (Watts units)

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG UL 2818



Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
533, 533HRC, 565 - 1.21 lbs/SF; 48 SF/ctn
563 - 1.33 lbs/SF; 40 SF/ctn
574, 574HRC - 1.10 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton, excludes Cirrus® High NRC panels

Metric Items Available
574M, 533M, 563M, 565M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.