

FINE FISSURED™ Second Look®

Scored Tegular
medium texture



Declare

UP TO **56%** RECYCLED CONTENT

LEED WELL | LBC

energy management, construction waste mgmt, regional materials, design for flexibility, EPD, recyclable/extended producer resp., biobased materials, recycled content, sourcing of raw materials, material ingredient reporting, low emitting materials, lighting quality, acoustics

LOCATION DEPENDENT

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

\$\$\$\$



Fine Fissured™ Second Look® II panels with Suprafine® XL® 9/16" suspension system

Economical panels; Scored plank or geometric visual with standard acoustical performance.

KEY SELECTION ATTRIBUTES

- Fine Fissured™ Second Look® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Geometric scored visuals
- Economical option to create a designer look
- Mold- and mildew-resistant surface
- 10-Year replacement panel available for item 1761
- 30-Year Limited System Warranty against visible sag, mold, and mildew



COLOR



FACE VIEW



Second Look I



Second Look II



Second Look III

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	Visual	Second Look
FINE FISSURED™ Second Look®	11	1760	24 × 48 × 3/4"		Second Look I
15/16" Angled Tegular		1761	24 × 48 × 3/4"		Second Look II
		1861	24 × 48 × 3/4"		Second Look II
		1762	24 × 48 × 3/4"		Second Look III
9/16" Angled Tegular	27	1765	24 × 48 × 3/4"		Second Look I
		1766	24 × 48 × 3/4"		Second Look II

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =											
0.55 35*	N/A	Class A	0.82	*	*	*	Std	Std	*	*	
0.55 35*	N/A	Class A	0.82	*	*	*	Std	Std	*	*	
0.55 35*	N/A	Fire Guard™	0.82	*	*	*	Std	Std	*	*	
0.55 35*	N/A	Class A	0.82	*	*	*	Std	Std	*	*	
0.55 30	N/A	Class A	0.82	*	*	*	Std	Std	*	*	
0.55 30	N/A	Class A	0.82	*	*	*	Std	Std	*	*	

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).
Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type III, Form 2, Pattern C E K
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



30-Year Performance Guarantee & Warranty
When installed with Armstrong® suspension system. Details at armstrongceilings.com/warranty

Design Consideration
Do not mix Fine Fissured™ Second Look® panels with standard Fine Fissured panels in the same room. It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.

Weight; Square Feet/Carton
0.75 lbs/SF; 80 SF/carton

Minimum Order Quantity
1 carton

Metric Items Available
1761M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/finefissured
BPCS-3027-123

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute™; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2023 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard

