

# FINE FISSURED™

Tile  
medium texture



**SUSTAIN®**  
High Performance  
Sustainable  
Ceiling Systems

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Fine Fissured™ tile with Prelude® Concealed 15/16" suspension system

Tiles have a grid-hiding, monolithic visual; Non-directional with standard acoustical performance and concealed or tongue-and-groove installation options.

## KEY SELECTION ATTRIBUTES

- 12" x 12" concealed tile option provides grid-hiding monolithic installation
- Non-directional visual reduces scrap and installation time
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Fine Fissured panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

new

## COLOR



White  
(WH)

# FINE FISSURED™

Tile  
medium texture



**GREENGUARD Gold Certified**  
(details below)

**Declare.**

**LEED WELL | LBC**

**56% RECYCLED CONTENT**

Calculate sustainability with Green Genie™ [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/repurposed producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
FINE FISSURED® Tile	66	746	12 x 12 x 5/8" □
<b>Concealed</b>			
Tongue-and-Groove	63	741	12 x 12 x 1/2" □

## PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Durability	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =							Fog				
0.55 35	N/A	Class A	0.82	*	*	*		Std	*	*	*
0.55	N/A	N/A	Class A	0.82	*	*		Std	*	*	*

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Splines not included in carton. Not recyclable when glue-up installation method is used.

## SUSPENSION SYSTEM

15/16" Concealed   
Prelude® Concealed or Adhesive

## STAPLE UP/ADHESIVE

Tongue-and-Groove

## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type III, Form 2, Pattern C E  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.



**Insulation Value**  
R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Square Feet/Carton**  
741 – 0.75 lbs/SF; 40 SF/ctn  
746 – 0.90 lbs/SF; 40 SF/ctn

**Minimum Order Quantity**  
1 carton

