

TUNDRA®

Square Lay-in & Tegular
medium texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Tundra® panels with Suprafine® XL® 9/16" suspension system

Medium-texture panels that are impact- and scratch-resistant, with standard sound absorption and high sound blocking.

KEY SELECTION ATTRIBUTES

- Durable
 - Impact-resistant
 - Scratch-resistant
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Tundra® Beveled Tegular
2. Tundra® with Suprafine® XL® 9/16" suspension system

TUNDRA®

Square Lay-in & Tegular medium texture

LEED® WELL™ LBC Up to **35% RECYCLED CONTENT**

Calculate sustainability with Green Genie® armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/excise producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

WELL Building Standard™ (WELL) Living Building Challenge® (LBC)

VISUAL SELECTION

| armstrongceilings.com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) |
|---------------------------------|--------------------|---|---------------------|
| TUNDRA® 15/16" Square Lay-in | 1 | 301 | 24 × 24 × 5/8" □ |
| | | 302 | 24 × 48 × 5/8" □ |
| 15/16" Beveled Tegular | 15 | 303 | 24 × 24 × 5/8" □ |
| | | 305 | 24 × 48 × 5/8" □ |
| 9/16" Beveled Tegular | 29, 44, 48, 52, 56 | 304 | 24 × 24 × 5/8" □ |
| | | | |
| Made-to-Order Sizes | | | |
| | | 5/8" Thick – 15/16" Square Lay-in, 9/16" & 15/16" Beveled Tegular | |
| | | Width | Length |
| | | 24" | 24" - 48" |

4-6 WEEKS
order to ship


PERFORMANCE SELECTION

Dots represent high level of performance.

| UL Classified Acoustics | Total Acoustics ¹ | Fire Performance | Light Reflect | Anti-Mold/Mildew | Sag Resistant | Certified Low VOC Emissions | DURABILITY | Recycled Content | Recycle Program | 30-Yr Warranty |
|-------------------------|------------------------------|------------------|---------------|------------------|---------------|-----------------------------|------------|------------------|-----------------|----------------|
| NRC + CAC = | | | | | | | Impact | Scratch | | |
| 0.50 33 | N/A | Class A | 0.86 | * | * | N/A | * | * | Std | * |
| 0.50 35 | N/A | Class A | 0.86 | * | * | N/A | * | * | Std | * |
| 0.50 33 | N/A | Class A | 0.86 | * | * | N/A | * | * | Std | * |
| 0.50 35 | N/A | Class A | 0.86 | * | * | N/A | * | * | Std | * |
| 0.50 33 | N/A | Class A | 0.86 | * | * | N/A | * | * | Std | * |
| N/A N/A | N/A | Class A | 0.86 | * | * | N/A | * | * | Std | * |

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed, high-density mineral fiber

Surface Finish
Factory-applied latex paint with scuff-resistant spatter coat

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Acoustical Testing
CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

Insulation Value
R Factor – 1.7 (BTU units)
R Factor – 0.30 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
301, 302, 305 – 1.09 lbs/SF; 64 SF/ctn
303, 304 – 1.10 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
302M, 303M, 305M, 304M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

