


ULTIMA® Health Zone™  
ULTIMA® Health Zone™ High NRC

Tegular  
fine texture



Ultima® Health Zone™ Tegular panels with Suprafine® 9/16" suspension system

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Perfect for education, office, and healthcare spaces

Fine texture mineral fiber ceiling; combines exceptional acoustical performance, sustainability, and functionality attributes in one go anywhere ceiling panel that is especially durable and aesthetically pleasing for every healthy space.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability and cleanability – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- Ultima® Health Zone™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems
- Long-lasting water-repellency; washable and scrubbable
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth
- 10-Year replacement panel available for item 1936



TYPICAL APPLICATIONS

- Healthcare:
  - Patient rooms
  - Treatment rooms
  - Nurses' stations
  - Emergency rooms
  - Corridors
  - Lavatories and restrooms
  - Kitchen/food prep areas
- Education
- Office
- Clean Rooms (item 1937)

COLOR



White  
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Ultima® Health Zone™ High NRC panel with Suprafine® XL® 9/16" suspension system
2. Ultima® Health Zone™ High NRC Square Tegular panel with Prelude® XL® 15/16" suspension system
3. Ultima® Health Zone™ High NRC Square Tegular with Interlude® XL® HRC 9/16" suspension system

# ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Tegular  
fine texture



Declare.



GREENGUARD Gold Certified (details below)

LEED® WELL™ LBC  
UP TO 76% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with Green Genie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® Health Zone™ High NRC	15, 16	1447	24 × 24 × 7/8" □
15/16" Beveled Tegular			
9/16" Beveled Tegular	29, 44, 48, 52, 56	1446	24 × 24 × 7/8" □
9/16" Beveled Tegular			
ULTIMA Health Zone	15, 16	1937	24 × 24 × 3/4" □
15/16" Beveled Tegular			
9/16" Beveled Tegular	29, 44, 48, 52, 56	1936	24 × 24 × 3/4" □
9/16" Beveled Tegular			
Made-to-Order Sizes			3/4" or 7/8" Thick – 9/16" & 15/16" Beveled Tegular
ULTIMA Health Zone			Width (short side): 4" – 30" Length (long side): 12" – 72"
ULTIMA Health Zone High NRC			

1 Ctn Min FASTSIZE 3 WEEKS order to ship

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

## PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics		Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Anti-Bacterial/Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY									
NRC	CAC	NRC CAC	AC	Class	Light Reflect	Anti-Bacterial/Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Fog & Spray	Wipe	Water Repel	Wash	Scrub	Impact	Scratch	Soil	30-Yr Warranty		
0.80	35	BEST	170	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*		
0.70	38	BETTER	N/A	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*		
0.70	38	BETTER	N/A	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*		
N/A	N/A	N/A	N/A	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*		



## SUSPENSION SYSTEMS



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber with DuraBrite® acoustically transparent water-repellent membrane

**Surface Finish**  
DuraBrite with factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL\* labeled).

**ASTM E1264 Classification**  
Type IV, Form 2, Pattern E; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Bacterial/Mold/Mildew**  
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
CAC testing conducted using Prelude suspension system for 15/16" edge profile and Silhouette® 9/16" profile.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG UL 2818



**Insulation Value**  
R Factor – 2.2 (BTU units)  
R Factor – 0.39 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
1936, 1937 – 1.08 lbs/SF; 48 SF/ctn  
1447, 1446 – 1.0 lbs/SF; 40 SF/ctn

**Minimum Order Quantity**  
1 carton

TechLine / 1 877 276-7876  
armstrongceilings.com/healthzone  
BPCS-5147-823

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates. © 2023 AWI Licensing LLC

**Armstrong®**  
World Industries

MINERAL FIBER – Standard