

ULTIMA®
ULTIMA® High NRC
Square Lay-in
fine texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Ultima Square Lay-in panels with Prelude XL 15/16" suspension system

Smooth-texture panels that are washable, impact- and scratch-resistant with a non-directional visual; offers both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Ultima® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface



- High sound absorption options available up to 0.85 NRC
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1910HRC, 1913HRC 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 95%
- Items available with AirGuard® coating which actively removes formaldehyde from indoor air
- Item 1910 available with Create!™ printed images and patterns

- Non-directional visual reduces scrap and installation time
- Compatible with the TechZone® Ceiling Systems
- 30-Year Limited System Warranty against visible sag
- 10-Year replacement panel available for items 1910, 1913
- Made in the U.S.A. of domestic and global content
- Build America, Buy America Act (BABAA) compliant



TYPICAL APPLICATIONS


- Offices – closed spaces for privacy and confidentiality; open spaces for focus, collaboration, and teaming
- Healthcare – assists in addressing HIPAA, HCAHPS, and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail

COLOR



White (WH)

DETAILS



1. Ultima® Square Lay-in
2. Ultima® Square Lay-in with Prelude® XL® 15/16" suspension system

ULTIMA® ULTIMA® High NRC

Square Lay-in
fine texture



LEED® WELL™ LBC

Up to **87% RECYCLED CONTENT**

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

energy management, construction waste mgmt, regional materials, design for flexibility, EPD, recyclable/inhale producer resp., biobased materials, recycled content, sourcing of raw materials, material ingredient reporting, low emitting/ materials, lighting quality, acoustics

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® High NRC 15/16" Square Lay-in		2080	24 x 24 x 1"
		2083	24 x 48 x 1"
		1940	24 x 24 x 7/8"
		1943	24 x 48 x 7/8"
		1432	24 x 60 x 7/8"
1435	24 x 72 x 7/8"		

7/8" & 1" Thick – 15/16" Square Lay-in

Made-to-Order Sizes	Width (short side)	Length (long side)	N/A	N/A	N/A	N/A	Class	0.87	*	*	*	*	*	*	*	*	*	*
Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com	4" – 30"	12" – 72"					Class	0.87	*	*	*	*	*	*	*	*	*	*

1 Ctn Min FASTSIZE 3 WEEKS order to ship

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program	30-Yr Warranty		
NRC + CAC	NRC CAC	AC	Fire	Light	Anti-Mold/Mildew	Sag Resistant	Fog	Wash	Impact	Scratch	Soil	Recycle
0.85 + 35	BEST	170	Class A	0.85	*	*	*	*	*	*	*	*
0.85 + 35	BEST	170	Class A	0.85	*	*	*	*	*	*	*	*
0.80 + 35	BEST	170	Class A	0.87	*	*	*	*	*	*	*	*
0.80 + 35	BEST	170	Class A	0.87	*	*	*	*	*	*	*	*
0.80 + 35	BEST	170	Class A	0.87	*	*	*	*	*	*	*	*
0.80 + 35	BEST	170	Class A	0.87	*	*	*	*	*	*	*	*

MORE ITEMS ▶

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

15/16" **Blizzard White – Suspension System Finish**
A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification
Type A5, Form 2, Pattern C, E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® XL® suspension system.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value
2083, 1940, 1943, 1432, 1435 – R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)
2080, 2081 – R Factor - 2.9 (BTU units); 0.445 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1940 – 1.14 LBS/SF; 40 SF/CTN
1943 – 1.125 LBS/SF; 48 SF/CTN
1432 – 1.05 LBS/SF; 60 SF/CTN
1435 – 1.04 LBS/SF; 72 SF/CTN
2080 – 1.0 LBS/SF; 40 SF/CTN
2083 – 1.0 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
1940M, 1943M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

ULTIMA® ULTIMA® High NRC

Square Lay-in
fine texture



LEED WELL LBC
UP TO **87% RECYCLED CONTENT**

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® 15/16" Square Lay-in		1420	6 × 48 × 3/4"
		1425	6 × 60 × 3/4"
		1990	12 × 48 × 3/4"
		1991	12 × 60 × 3/4"
		1992	12 × 72 × 3/4"
		1910	24 × 24 × 3/4"
		1910HRC**	24 × 24 × 3/4"
		1913	24 × 48 × 3/4"
		1913HRC**	24 × 48 × 3/4"
		1984	24 × 60 × 3/4"
1980	24 × 72 × 3/4"		

Made-to-Order Sizes	Width (short side)	Length (long side)
4" - 30"	12" - 72"	

3/4" Thick - 15/16" Square Lay-in

1 Ctn Min FASTSIZE 3 WEEKS order to ship

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics*	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program			
NRC + CAC	NRC CAC							Fog	Wash	Impact	Scratch	Soil	30-yr Warranty
N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*
N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*
0.65*	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*
0.65*	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*
0.65*	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*
0.75	35	BETTER	Class A	0.88	*	*	*	*	*	*	*	*	*
0.75	35	BETTER	Class A	0.88	*	*	*	*	*	*	*	*	*
0.75	35	BETTER	Class A	0.88	*	*	*	*	*	*	*	*	*
0.75	35	BETTER	Class A	0.88	*	*	*	*	*	*	*	*	*
N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*

* Total Acoustics* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

* Items are not UL* classified

** Ceiling-2-Ceiling™ Post-consumer Recycled Content options

SUSPENSION SYSTEMS

15/16" **Blizzard White - Suspension System Finish**
A color and texture coordinated suspension system to complement Ultima ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification
Type A5, Form 2, Pattern C, E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® XL® suspension system.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value
R Factor - 2.2 (BTU units); R Factor - 0.39 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options

available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1420, 1425 - 1.05 LBS/SF; 24 SF/CTN
1910, 1910HRC, 1913, 1913HRC - 1.08 LBS/SF; 48 SF/CTN
1991 - 1.08 LBS/SF; 30 SF/CTN
1992 - 1.08 LBS/SF; 36 SF/CTN
1980 - 1.08 LBS/SF; 72 SF/CTN
1990 - 1.08 LBS/SF; 24 SF/CTN
1984 - 1.08 LBS/SF; 80 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
1910M, 1913M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER - Standard

ULTIMA® ULTIMA® High NRC

Square Lay-in
fine texture



Declare.

LEED® WELL | LBC

Up to 87% RECYCLED CONTENT

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/repurposed producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® with AirGuard™ Coating 15/16" Square Lay-in		1900	24 x 24 x 3/4" □
AirGuard™ Coating actively removes formaldehyde from indoor air.		1903	24 x 48 x 3/4" □

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program
NRC	CAC	NRC CAC							Fog	Wash	Impact	Scratch	Soil	30-Yr Warranty	
0.75	35	BETTER	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*	
0.75	35	BETTER	N/A	Class A	0.88	*	*	*	*	*	*	*	*	*	

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

15/16" **Prelude®** Blizard White – Suspension System Finish
A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type A5, Form 2, Pattern C, E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® XL® suspension system.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value
R Factor – 2.2 (BTU units); R Factor – 0.39 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1900, 1903, – 1.08 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

