

Armstrong acoustical panels with USAI Lighting Connect light fixtures

This pre-engineered suspension system seamlessly integrates recessed downlights at the intersection of the ceiling grid, placing light where it has never been before.

KEY SELECTION ATTRIBUTES

- Lighting and architecture perfectly integrated into the ceiling to deliver your vision of symmetry
- Replaces inconsistent finishes and edge details with clean crisp factory finished panels and grid for a fast and easy installation
- Compatible with the USAI Lighting CONNECT™ Family
- Eliminates the worry of field modified panels and grid

· Seismic code compliant

· Armstrong 10-Year Limited Warranty

COLORS





White (WH)

Blizzard White†† (ZW)

Follow the three (3) steps when specifying Intersection Downlighting:

1. Choose your ceiling system layout


2' x 2' Ceiling layout with lights 4' apart



2' x 2' Ceiling layout with lights 6' apart




2' x 2' Ceiling layout with lights 8' apart



30" x 30" Ceiling layout with lights 5' apart



30" x 30" Ceiling layout with lights 7.5' apart





LIGHTING SOLUTIONS

Intersection Downlighting for Acoustical Ceilings


2. Choose your 9/16" Intersection Profile Downlighting Kit (main beams, standard cross tees, wall molding, and lights need to be ordered separately)

Choose Hub Kit, then appropriate cross tee module

	Item No.◆	Description		Item No.◆	Description
Silhouette® XL® 1/4" Reveal	76D4SK	4" Downlight Hub Kit w/ Yokes & hardware	Suprafine® XL®	75D4SK	4" Downlight Hub Kit w/ Yokes & hardware
	XL7622DL	24" Module Downlight Cross Tee	_	XL7522DL	24" Module Downlight Cross Tee
	XL7628DL	30" Module Downlight Cross Tee		XL7528DL	30" Module Downlight Cross Tee
Silhouette XL 1/8" Reveal	768D4SK	4" Downlight Hub Kit w/ Yokes & hardware	Interlude® XL® HRC	61D4SK	4" Downlight Hub Kit w/ Yokes & hardware
	XL76822DL	24" Module Downlight Cross Tee	_	XL6122DL	24" Module Downlight Cross Tee
	XL76828DL	30" Module Downlight Cross Tee	_	XL6128DL	30" Module Downlight Cross Tee
			_		

8' Cross tee - Notched 48" O.C. available Made-to-Order

KIT COMPONENTS INCLUDED (8 KITS PER CARTON)



(1) High-Profile Yoke (not assembled – comes in two pieces)*




(2) Cross Tee Connection Clips



(1) Downlight Suspension Frame

ACCESSORIES





FZD4YKLP Low-Profile Yoke



SH1206
PeakForm® Support Hanger with Routing 6" O.C.

INTERSECTION DOWNLIGHTING ASSEMBLY/CEILING PANEL LAYOUT





NOTE: These are directional panels and come as (8) pieces per carton (4 As / 4 Bs marked)



 $[\]spadesuit$ Add the 2-letter color suffix to the item number when specifying or ordering (Example: AX2WEC \underline{Z} $\underline{W})$

LIGHTING SOLUTIONS

Intersection Downlighting for **Acoustical Ceilings**

3. Choose your Ceiling Panel Notched Calla® and Ultima® ceiling panels (24" x 24" tegular panels for 9/16" grid) also available as a special order.

VISUAL SELECTION PERFORMANCE SELECTION Dots represent high level of performance. DURABILITY Total Acoustics¹ (H) **UL** Classified Acoustics Edge Item Dimensions Profile No. (Inches) CALLA® 9/16" 170 Class 0.86 2818 24 × 24 × 1' 0.85 35 BEST Square Notched ((()) . Tegular **Ceiling Panels** CALLA® 9/16" 2824 0.85 $24 \times 24 \times 1$ 35 BEST 170 Class 0.86 Square Compatable ((()) Tegular Full-Size Panels 9/16" Square Tegular N/A Intersection Visual Downlighting Ultima® 24 × 24" Ceiling Ultima High NRC 24 × 24 Panels/ 30 × 30' Calla 1 Notch Ultima 30 × 30" Ultima High NRC 30 × 30'

CONNECT™ FAMILY

The aesthetic and uncompromising craftsmanship of the Connect™ Lighting system integrates beautiful illumination with simplicity.



LIGHTING FIXTURES

For more product information visit: usailighting.com/connect

PHYSICAL DATA

Material

Cross Tees: Hot-dipped galvanized steel High-Profile Yoke: Galvanized steel Low-Profile Yoke: Galvanized steel Cross Tee Connector Clip: Galvanized steel Downlight Suspension Frame: ADC12 Aluminum Surface Finish

Baked polyester paint or powder-coated finish

Cross Tee / Downlight Suspension Frame Interface Flush

End detail Staked-on XL Clip

Installation Considerations

The high-profile yoke included in each kit is designed for use with the USAI Lighting CONNECT Family Downlight, Adjustable, and Wall Wash lighting options.

For low plenum installations, the low-profile yoke can be ordered separately and comes with (8) eight unassembled yokes. The low-profile yoke can be used with the USAI CONNECT Family Downlight and Wall Wash options. A lowprofile yoke will not fit the housing of a USAI CONNECT adjustable downlight and a high-profile yoke must be used.

Downlight Suspension Frame can only receive directional cross tees. For light spacing 6' apart alternate main beam spacing (4' spacing, 2' spacing).

Downlight Hub Kit Components

Each carton contains (8) eight Intersection Downlighting Kits with the following components:

(8) High-Profile Yokes (unassembled)

(8) Downlight Suspension Frames

(20) Cross Tee Connection Clips (16 clips are required,

4 extra per carton)

Module Cross Tee Kits (32) cross tees per carton

Warranty 10-year limited warranty



¹ Total Acoustics* ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+) NOTE: Item # 2824 is the compatible full-size (24" x 24" x 1") panel