

OPTIMA® Health Zone™
 OPTIMA® PB Health Zone™
 with Plant-based Binder
 Square Lay-in
 smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Optima® Health Zone™ Square Tegular panels with Prelude® XL® 15/16" suspension system

Perfect for office, education, and healthcare spaces

Fine texture ceiling; combines exceptional acoustical absorption for open plan spaces, sustainability, and functionality attributes in one panel that is especially durable and aesthetically pleasing for every healthy space.

KEY SELECTION ATTRIBUTES

- Optima® PB Health Zone™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Items with PB suffix are manufactured with a plant-based binder
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability and cleanliness – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- Meets or exceeds USDA/FSIS and FGI guidelines
- Clean room performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems (items 3114, 3115)
- Meets ISO Class 5 particulate shedding requirements; not suitable for use in pressurized environments
- Long-lasting water-repellency; washable and scrubbable
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

TYPICAL APPLICATIONS

- Healthcare:
- Assists in addressing HIPAA, HCAHPS, and FGI Guidelines
 - Patient rooms (walls-to-deck)
 - Treatment rooms (walls-to-deck)
 - Nurses' stations
 - Emergency rooms
 - Semi-restricted surgical areas
 - Kitchens/food preparation areas
 - Laboratories
- Education
- Office
- Clean Rooms (Items 3214, 3215)
- Medical facilities
 - Data centers

COLOR



White (WH)

DETAILS



1. Optima® Health Zone™ Square Lay-in
2. Optima® Health Zone™ Square Lay-in with Clean Room™ 15/16" suspension system

OPTIMA® Health Zone™
OPTIMA® PB Health Zone™
with Plant-based Binder
Square Lay-in
smooth texture



LEED® WELL™ LBC
UP TO 71% RECYCLED CONTENT
energy management, construction waste mgmt, regional materials, design for flexibility, EPD, recyclable/producer resp., biobased materials, recycled content, sourcing of raw materials, material ingredient reporting, low emitting materials, lighting quality, acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
OPTIMA® Health Zone™	1, 6, 7	3114PB*	24 × 24 × 1"
15/16" Square Lay-in		3314	24 × 24 × 1-1/2"
		3115PB*	24 × 48 × 1"
		3315	24 × 48 × 1-1/2"

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	CAC =	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Bacterial/Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels		DURABILITY							30-Yr Warranty				
									Fog & Spray	Wipe	Water Repel	Wash	Scrub	Impact	Scratch	Soil						
0.95	N/A	N/A	190	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
0.95	29	N/A	190	Class A	0.86	+	*	N/A	*	*	*	*	*	*	*	*	*	*	*	*	*	*
0.95	N/A	N/A	190	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
0.95	29	N/A	190	Class A	0.86	+	*	N/A	*	*	*	*	*	*	*	*	*	*	*	*	*	*

1 Ctn Min FASTSIZE 3 WEEKS order to ship

Made-to-Order Sizes
Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

PB 1" Thick – 15/16" Square Lay-in

Width (short side)	Length (long side)	N/A	N/A	N/A	N/A	Class A	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	
4" – 47-1/2"	9" – 48"																					

Non-PB 1" Thick – 15/16" Square Lay-in


Width (short side)	Length (long side)	N/A	N/A	N/A	N/A	Class A	0.86	+	*	N/A	*	*	*	*	*	*	*	*	*	*	*	
4" – 47-1/2"	9" – 48"																					

Non-PB 1-1/2" Thick – 15/16" Square Lay-in

Width (short side)	Length (long side)	N/A	N/A	N/A	N/A	Class A	0.86	+	*	N/A	*	*	*	*	*	*	*	*	*	*	*	
4" – 47-1/2"	9" – 48"																					

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
* Item provides Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
3114PB, 3115PB – Fiberglass with DuraBrite® scrim acoustically transparent membrane.
3314, 3315 – Fiberglass with DuraBrite acoustically transparent membrane; CAC backing.
Surface Finish
DuraBrite with factory-applied latex paint
Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).
ASTM E1264 Classification
Type B, Form B2, Pattern E; Fire Class A
Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.
Anti-Bacterial/Mold/Mildew
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

VOC Emissions (PB suffix items only)
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.
High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.
Insulation Value
R Factor – 4.0 (BTU units)
R Factor – 0.70 (Watts units)

Application Considerations
For Clean Room installations, use full-size panels. Testing for Clean Room 5 (Class 100) was completed with full-size 15/16" gasketed suspension system. For Clean Rooms that require field-cut perimeter panels, use Lay-in panels (3114, 3115) or Tegular panels (3214, 3215) with Lay-in field-cut panels at the perimeter. Meets ISO Class 5 particulate shedding requirements; not suitable for use in pressurized environments.
Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning
30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty
Weight; Square Feet/Carton
3114PB – 0.46 LBS/SF; 48 SF/CTN
3115PB, 3315 – 0.45 LBS/SF; 96 SF/CTN
3314 – 0.67 LBS/SF; 32 SF/CTN
Minimum Order Quantity
1 carton



FIBERGLASS – Standard