PAINTED NUBBY™

Square Lay-in & Tegular medium texture



CAD/Revit® drawings at: armstrongceilings.com/cadrevit

Painted Nubby panels with Prelude® XL® 15/16" suspension system

Medium-textured panels with a medium-textured fabric visual that offers high sound absorption.

KEY SELECTION ATTRIBUTES

- Outstanding acoustical performance; both Articulation Class 180-190 and NRC 0.85-0.95
- · Fiberglass substrate resists mold and mildew
- · Mold- and mildew-resistant surface
- · 30-Year Limited System Warranty against visible sag, mold, and mildew
- · Made in the U.S.A. of domestic and global content
- · Build America, Buy America (BABA) Act compliant

COLOR



White (WH)

DETAILS





- 1. Painted Nubby™ Tegular
- 2. Painted Nubby™ Tegular with Silhouette® XL® 9/16" suspension system 1/4" reveal

Armstrong[®] World Industries


Square Lay-in & Tegular medium texture



VISUAL SELECTION					PERFORMANCE SELECTION Dots represent high level of performance.										\$	\$\$\$\$	
armstrongceilings. com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)			n) ssified sstics + CAC =	Total Acoustics¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/ Anti-Mold/ Mildew	Sag Hesistant Resistant	Certified Low VOC Emissions	Durability	Recycled Content	30-Yr Warranty	
PAINTED NUBBY™ 15/16" Square Lay-in	1	3102	24 × 24 × 1"		0.95	N/A	N/A	190	Class A	0.82	٠	٠	N/A	Std	٠	•	
		3101	24 × 48 × 3/4	4"	0.85	N/A	N/A	180	Class A	0.82	٠	•	N/A	Std	٠	٠	
		3103	24 × 48 × 1"		0.95	N/A	N/A	190	Class A	0.82	٠	•	N/A	Std	٠	•	
		3104	48 × 96 × 1"		0.95	N/A	N/A	190	Class A	0.82	۰	٠	N/A	Std	٠	•	
15/16" Square Tegular	8	3200	24 × 24 × 1"		0.95	N/A	N/A	190	Class A	0.82	۰	0	N/A	Std	٠	۰	
9/16" Square Tegular	26, 43, 47, 51, 55	3201	24 × 24 × 1"		0.95	N/A	N/A	190	Class A	0.82	٠	٠	N/A	Std	٠	•	
		3/4" or 1	I" Thick - 9/16	5" or 15/16" Squ	are Tegul	ar											
	3-4 VEEKS der to ship	Width 4" - 48"	Len-	120"	0.95	N/A	N/A	190	Class A	0.82	٠	٠	N/A	Std	٠	٠	

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Fiberglass with fabric facing

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification

Type B, Form 2, Pattern F; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details

A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value

3101 - R Factor - 3.0 (BTU units) R Factor - 0.53 (Watts units) 3102, 3103, 3104, 3200, 3201 -R Factor - 4.0 (BTU units) R Factor - 0.70 (Watts units)

30-Year Performance Guarantee & Warranty When installed with Armstrong® Suspension System.

Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton 3101 - 0.44 LBS/SF; 128 SF/CTN 3102, 3103 - 0.46 LBS/SF; 96 SF/CTN 3104 - 0.46 LBS/SF; 128 SF/CTN 3200, 3201 - 0.46 LBS/SF; 48 SF/CTN

Minimum Order Quantity

1 carton, excludes made-to-order panels

Metric Items Available

3102M, 3101M, 3103M, 3200M, 3201M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

