

# PAINTED NUBBY™

Square Lay-in & Tegular  
medium texture

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Painted Nubby™ panels with Prelude® XL® 15/16" suspension system

Medium-textured panels with a medium-textured fabric visual that offers high sound absorption.

## KEY SELECTION ATTRIBUTES


- Outstanding acoustical performance; both Articulation Class 180-190 and NRC 0.85-0.95
- Fiberglass substrate resists mold and mildew
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

## COLOR



White  
(WH)

## DETAILS



1. Painted Nubby™ Tegular

2. Painted Nubby™ Tegular with Silhouette® XL® 9/16" suspension system 1/4" reveal

# PAINTED NUBBY™

Square Lay-in & Tegular  
medium texture

LEED® WELL | LBC

UP TO 71% RECYCLED CONTENT

Calculate sustainability with Green Genie®  
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
PAINTED NUBBY™ 15/16" Square Lay-in	1	3102	24 × 24 × 1"
		3101	24 × 48 × 3/4"
		3103	24 × 48 × 1"
		3104	48 × 96 × 1"
15/16" Square Tegular	8	3200	24 × 24 × 1"
9/16" Square Tegular	26, 43, 47, 51, 55	3201	24 × 24 × 1"
Made-to-Order Sizes			3/4" or 1" Thick – 9/16" or 15/16" Square Tegular
			Width: 4" - 48"      Length: 4" - 120"

**3-4 WEEKS**  
order to ship

## PERFORMANCE SELECTION


Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	30-Yr Warranty
0.95	N/A	N/A	190	Class A	0.82	*	*	N/A	Std	*
0.85	N/A	N/A	180	Class A	0.82	*	*	N/A	Std	*
0.95	N/A	N/A	190	Class A	0.82	*	*	N/A	Std	*
0.95	N/A	N/A	190	Class A	0.82	*	*	N/A	Std	*
0.95	N/A	N/A	190	Class A	0.82	*	*	N/A	Std	*
0.95	N/A	N/A	190	Class A	0.82	*	*	N/A	Std	*

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

## SUSPENSION SYSTEMS



## PHYSICAL DATA

**Material**  
Fiberglass with fabric facing

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type XII, Form 2, Pattern E  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Acoustical Details**  
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

**Insulation Value**  
3101 – R Factor - 3.0 (BTU units)  
R Factor - 0.53 (Watts units)  
3102, 3103, 3104, 3200, 3201 – R Factor - 4.0 (BTU units)  
R Factor - 0.70 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
3101 – 0.44 lbs/SF; 128 SF/ctn  
3102, 3103 – 0.46 lbs/SF; 96 SF/ctn  
3104 – 0.46 lbs/SF; 128 SF/ctn  
3200, 3201 – 0.46 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels

**Metric Items Available**  
3102M, 3101M, 3103M, 3200M, 3201M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.