

PEBBLE™
Square Lay-in
medium texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Pebble™ panel with Prelude® XL® 15/16" suspension system

Economical, medium-textured panels have an easy-to-clean, durable surface with high sound absorption options.

KEY SELECTION ATTRIBUTES


- High sound absorption - up to 0.80 NRC (perforated panels only)
- Easy-to-clean, durable surface - Impact-, Scratch-, and Soil-resistant, and scrubbable
- Economical solution
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR



White
(WH)

DETAILS



1. Pebble™
2. Pebble™ with Prelude® XL® 15/16" suspension system

PEBBLE™

Square Lay-in
medium texture

LEED® WELL™ LBC

UP TO **71% RECYCLED CONTENT**

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

VISUAL SELECTION

| armstrongceilings.com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) | |
|---------------------------------------|------------|----------|-----------------------------------|-----------|
| PEBBLE™ High NRC (Perforated) | 1 | 2988 | 24 × 24 × 1" | |
| 15/16" Square Lay-in | | 2989 | 24 × 48 × 1" | |
| Made-to-Order Sizes | | | 1" Thick – 15/16" Square Lay-in | |
| PEBBLE™ High NRC (Perforated) | | | Width | Length |
| | | | 12" - 30" | 12" - 60" |
| PEBBLE™ (Perforated) | 1 | 2983 | 24 × 48 × 5/8" | |
| 15/16" Square Lay-in | | 2970 | 24 × 60 × 5/8" | |
| PEBBLE™ (Perforated and Unperforated) | 1 | 2968 | 24 × 48 × 5/8" | |
| 15/16" Square Lay-in | | | 5/8" Thick – 15/16" Square Lay-in | |
| Made-to-Order Sizes | | | Width | Length |
| | | | 12" - 30" | 12" - 60" |
| PEBBLE™ (Unperforated) | | | | |

3-4 WEEKS
order to ship

3-4 WEEKS
order to ship


PERFORMANCE SELECTION

Dots represent high level of performance.

| UL Classified Acoustics | | Total Acoustics ¹ | Fire Performance | Light Reflect | Anti-Mold/Mildew | Sag Resistant | Certified Low VOC Emissions | Water Repel | DURABILITY | | | | Recycled Content | 30-Yr Warranty |
|-------------------------|---------|------------------------------|------------------|---------------|------------------|---------------|-----------------------------|-------------|------------|-------|--------|------|------------------|----------------|
| NRC | + CAC = | | | | | | | | Wash | Scrub | Impact | Soil | | |
| 0.80 | N/A | N/A | Class A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |
| 0.80 | N/A | N/A | Class A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |
| N/A | N/A | N/A | N/A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |
| 0.70 | N/A | N/A | Class A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |
| 0.70 | N/A | N/A | Class A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |
| 0.50 | N/A | N/A | Class A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |
| N/A | N/A | N/A | N/A | 0.87 | * | * | N/A | N/A | * | * | * | * | * | * |

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type XII, Form 1, Pattern E C
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
2968, 2970, 2983 - R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)
2988, 2989 - R Factor - 4.0 (BTU units)
R Factor - 0.70 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
2968, 2983 - 0.20 lbs/SF; 128 SF/ctn
2970 - 0.20 lbs/SF; 120 SF/ctn
2988, 2989 - 0.31 lbs/SF; 80 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels.

Metric Items Available
2983M, 2970M, 2988M, 2989M, 2968M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.