

CUSTOM WALL SYSTEMS

TECTUM® Fabric

Acoustical Wall Panels

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 98%

LEED®
WELL™ | LBC

energy
management

construction
waste mgmt

regional
materials

design for
flexibility

EPD

recyclable/
extended
producer resp.

biobased
materials

recycled
content

sourcing of
raw materials

material
ingredient
reporting

low emitting/
materials

lighting
quality

acoustics

LOCATION DEPENDENT



Tectum® Fabric Walls



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Tectum® Fabric Walls help control noise and are ideal in open-plan, mixed-use spaces.

KEY SELECTION ATTRIBUTES

- Abuse-resistant, fabric wrapped panels attach directly to walls
- Excellent Sound Absorption – NRC up to 0.90
- Panel sizes in 1", 1-1/2", or 2" thickness; widths: 23-3/4" to 47-3/4"; lengths: 48" to 120"
- Tackable panels can be used for bulletin/display boards
- Mounting is quick and easy using internal spline system
- USDA Biobased Content: 98%
- Long lasting, durable fabric options available
- Fabric wrapped to kerf, edges unfinished

FABRICS

For standard fabrics, refer to our website at:
armstrongceilings.com/tectum



Custom Fabric
Options Available

Product	Panel Thickness	Acoustics			Weight (Sq. Ft)
		A Mounting NRC	D-20 Mounting NRC	C-40 Mounting NRC	
Fabric Walls	1"	0.50	0.60	0.90	1.63 lbs/SF

PARTITIONS & WALLS