

Safety Data Sheet

according to OSHA Hazard Communication
29 CFR Part 1910.1200

Section 1. Identification

Product Information: 72W-A234

Product Name: ARMSTRONG ACCOUSTIBUILT DEW354 FINE TEXTURE FINISH

Recommended Use: Liquid Paint

Application Method: See Technical Data Sheet

Supplied by: Aexcel Corporation
7373 Production Drive. Mentor, OH 44060

Emergency Telephone: Chemtel: 800-255-3924

Section 2. Hazard(s) identification

GHS Classification
STOT RE 1

Symbol(s) of Product



Signal Word
Danger

GHS HAZARD STATEMENTS

STOT, repeated exposure, category 1 H372 Causes damage to organs through prolonged or repeated exposure.

GHS LABEL PRECAUTIONARY STATEMENTS

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P314 Get medical advice/attention if you feel unwell.
P501 Dispose of contents/container in accordance with local rules and regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P270 Do not eat, drink or smoke when using this product.

Section 3. Composition/Information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
CALCIUM CARBONATE	1317-65-3	10-25	GHS08	H372
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1-1.0	GHS08	H372
TITANIUM DIOXIDE	13463-67-7	10- 25	NI	NI

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air. Oxygen or artificial respiration if needed.

FIRST AID - SKIN CONTACT: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

FIRST AID - EYE CONTACT: Flush eye(s) immediately with plenty of water.

FIRST AID - INGESTION: Never give anything by mouth to an unconscious person. If ingested, consult a physician.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

SPECIAL FIREFIGHTING PROCEDURES: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Foam, Water Fog

Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Section 7. Handling and storage



HANDLING: Containers of this material may be hazardous when emptied. All metal parts of the mixing and processing equipment must be grounded. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not re-use empty containers. Keep away from food and drink. Keep away from open flames, hot surfaces and sources of ignition.

STORAGE: Harmful - Store away from foodstuffs. Perishable if frozen. Keep from freezing. For industrial use only.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
CALCIUM CARBONATE	15 mg/m ³	N.E.	15 mg/m ³	N.E.
CRYSTALLINE SILICA (QUARTZ)	.025 mg/m ³	N.E.	.025 mg/m ³	N.E.
TITANIUM DIOXIDE	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.



HYGIENIC PRACTICES: General industrial hygiene practice.

Section 9. Physical and Chemical Properties

Boiling Range:	212 - 482 Deg. F.	Vapor Density:	NE
Odor:	Pungent	Odor Threshold:	NE
Appearance:	Heavy Liquid	Evaporation Rate:	NE
Solubility in Water:	NE	Specific Gravity:	1.840
Freeze Point:	NE	pH:	NE
Vapor Pressure:	NE	Viscosity:	NE
Physical State:	Liquid	Flash Point, °F:	> 200 Deg.

(See section 16 for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Avoid contact with skin, eyes and clothing.

INCOMPATIBILITY: Incompatible with strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if stored and applied as directed.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Direct skin contact may cause moderate irritation and possibly dermatitis. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1317-65-3	CALCIUM CARBONATE	N.I.	N.I.	N.I.
14808-60-7	CRYSTALLINE SILICA (QUARTZ)	N.I.	N.I.	N.I.
13463-67-7	TITANIUM DIOXIDE	N.I.	N.I.	N.I.

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

Section 13. Disposal considerations



Product

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping	Paint, Latex
DOT Technical Name:	Paint
DOT Hazard Class:	Non-Hazardous
DOT UN/NA Number:	Non-Regulated

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories: Chronic Health Hazard

SARA SECTION 312:

<u>Chemical Name</u>	<u>CAS-No.</u>
CRYSTALLINE SILICA (QUARTZ)	14808-60-7
SODIUM HYDROXIDE	1310-73-2
TETRAHYDRO-3,5-DIMETHYL-2H-1,3,5-THIADIAZINE-2-THIONE	533-74-4

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
TETRAHYDRO-3,5-DIMETHYL-2H-1,3,5-THIADIAZINE-2-THIONE	533-74-4
PROPICONAZOLE	60207-90-1

TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

U.S. State Regulations:**NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
WATER	7732-18-5
CALCIUM CARBONATE	1317-65-3

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
ALUMINUM TRIHYDRATE	21645-51-2
D.I. WATER	7732-18-5
ACRYLIC COPOLYMER POLYVINYL	
CALCIUM CARBONATE	1317-65-3
CRISTOBALITE	14464-46-1

CALIFORNIA PROPOSITION 65 CARCINOGENS

WARNING

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
CRYSTALLINE SILICA (QUARTZ)	14808-60-7
TITANIUM DIOXIDE	13463-67-7
ACETALDEHYDE ANHYDROUS	75-07-0

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

None

International Regulations: As follows -**CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date: 05/02/2022 Supersedes Date: NEW
Reason for revision: GHS
Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	0	Reactivity:	0	Personal Protection:	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

Volatile Organic Compounds, gr/ltr: 0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H372 Causes damage to organs through prolonged or repeated exposure.

GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information