


ULTIMA® Health Zone™
ULTIMA® Health Zone™ High NRC

Tegular
fine texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Ultima® Health Zone™ Tegular panels with Silhouette® 9/16" suspension system

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Smooth-texture panels that are water repellent; Meet USDA/FSIS, FGI and HIPAA guidelines plus Clean Room assemblies. Offer both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Ultima® panels are part of the Sustain® portfolio, and meet the most stringent sustainability compliance standards today
- Clean Rooms up to ISO Class 5 (Class 100) (items 1935 & 1937)
- new** • CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Bacteria-resistant surface
- Exceeds FGI Guidelines for acoustics and cleanability in general healthcare spaces
- Meets USDA/FSIS guidelines for use in food processing areas
- Long-lasting water-repellency; Washable and Scrubbable
- USDA-Certified Biobased Product – 95%
- Smooth, clean, durable finish – Impact-, Scratch-, and Soil-resistant; safe for use with disinfectants
- Excellent sound absorption
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

TYPICAL APPLICATIONS

- Clean Rooms (item 1937)
Healthcare:
- Patient rooms
 - Treatment rooms
 - Nurses' stations
 - Emergency rooms
 - Corridors
 - Lavatories and restrooms
 - Kitchen/food prep areas
- Education
Office

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Ultima® Health Zone™ High NRC panel with panel Suprafine® XL® 9/16" suspension system
2. Ultima® Health Zone™ High NRC Square Tegular panel with Prelude® XL® 15/16" suspension system
3. Ultima® Health Zone™ High NRC Square Tegular with Interlude® XL® HRC 9/16" suspension system

ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Tegular
fine texture

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 95%

SUSTAIN™
High Performance
Sustainable Ceiling Systems

Declare.

GREENGUARD
Gold Certified
(details below)

LEED®
WELL™ LBC

UP TO 76% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/pre-consumer producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® Health Zone™ High NRC	15, 16	1447	24 x 24 x 7/8"
15/16" Beveled Tegular			
9/16" Beveled Tegular	29, 44, 48, 52, 56	1446	24 x 24 x 7/8"
ULTIMA Health Zone	15, 16	1937	24 x 24 x 3/4"
15/16" Beveled Tegular			
9/16" Beveled Tegular	29, 44, 48, 52, 56	1936	24 x 24 x 3/4"
Made-to-Order Sizes			
ULTIMA Health Zone			

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

3/4" Thick – 9/16" & 15/16" Beveled Tegular

Width	Length
4" – 6"	12" – 72"
6-1/2" – 30"	4" – 72"
30-1/2" – 48"	4" – 30"

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email TechLine@armstrongceilings.com

† Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Bacterial/Mold/Mildew	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program
0.80	35	BEST	170 Class A	0.86	+
0.70	38	BETTER	N/A Class A	0.86	+
0.70	35	BETTER	N/A Class A	0.86	+
N/A	N/A	N/A	N/A Class A	0.86	+

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent water-repellent membrane

Surface Finish
DuraBrite with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® suspension system for 15/16" edge profile and Silhouette® 9/16" profile.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



Insulation Value
R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1936, 1937 – 1.08 lbs/SF; 48 SF/ctn
1447, 1446 – 1.0 lbs/SF; 40 SF/ctn

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/ultimahealthzone
BPCS-5147-1020

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute®; WELL™ and Well Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2020 AWI Licensing LLC

Armstrong®
CEILING & WALL SOLUTIONS



MINERAL FIBER – Standard